

### PRODUCT DESCRIPTION

Is a slowly evaporating solvent thinner for single pack Welesgard coatings.

### FEATURE

- The thinner WG-Welethinner should be used at temperatures between 0 and 55 ° C.

### RECOMMENDED TO USE

Recommended to use for thinning of single pack moisture cured polyurethane, alkyd and acrylic Welesgard coatings.

### TECHNICAL DATA

Appearance	
Colour:	Transparent
Material properties	
Density (at +20 °C):	0.9 ± 0.05 g/cm
Flash Point	27°C ± 2 (Setaflash)
Determination of water, Karl Fischer method, ISO 12937	<0.04%

### AMBIENT CONDITIONS

As per TDS of the paint product.

### APPLICATION DATA

Add to paint material and stirred thoroughly before with low speed mixer in order to achieve its fully homogeneous condition.

#### Cleaning:

Could be used as a cleaner.

### PACKAGING

Volume (liters)	Size of containers (liters)
10/20	10/20

### STORAGE & SHELF LIFE

The product must be stored in original sealed containers. The storage conditions are to keep the containers in a dry, well ventilated space away from source of heat and/or ignition.

Storage temperature:	from 5 to 25°C
Shelf Life	2 years

### SAFETY

Use with adequate ventilation. Do not inhale aerosol. Avoid contact with skin. After contact with skin, wash immediately with detergent, soap and water. In case of contact with eyes, rinse immediately with water and seek medical advice immediately.

**For detailed information on the health and safety protection for use of this product, see Safety Data Sheet (SDS).**

### IMPORTANT NOTE

The above-mentioned information is given according to our laboratory tests and practical application experience. The manufacturer takes into consideration the fact that the material can be used out of control; the manufacturer cannot give guarantees except of the material quality. The manufacturer has the right to improve the product and change the above-mentioned data without preliminary notification.

**THE PRESENT TECHNICAL DATA SHEET REPLACES ALL PREVIOUS EDITIONS.**